2026 CAN-AM MAVERICK X3 X RC TURBO RR



PACKAGE HIGHLIGHTS

- Smart-Lok™* front differential
- FOX† 2.5 and FOX† 3.0 PODIUM RC2† shocks with bypass
- · Belt monitoring system
- 850 W magneto
- 32 in. XPS Hammer King tyres
- 15 in. aluminum beadlock wheels
- 4-point harness with shoulder pads
- Front bumper, half-doors, full hard roof, intrusion bar
- 4,500 lb (2,041.2 kg) winch with synthetic cable
- HMWPE differential and under bumper skid plates
- HMWPE front and rear suspension arm
- UHMWPE rock sliders
- Rear tow hook
- · 10.25 in. touchscreen display
- X-package graphics/seats
- Can-Am LED signature lights
- New skid plate and anti branch intrusion
- 2 person seating capacity

ENGINE	TURBO DR
ENGINE	TURBO RR
Туре	200 hp, Rotax* ACE (Advanced Combustion Efficiency) 900 cc turbocharged triple-cylinder engine, liquid-cooled with integrated intercooler and high-performance air filter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	pDrive primary and Quick Response System X (QRS-X) CVT with high airflow, L / H / N / R / P
Drive Train	Lockable front differential with exclusive Smart-Lok™* technology True 4-mode traction system: 2WD / 4WD with front diff. lock / 4WD ROCK / 4WD TRAIL
Power Steering	High torque Tri-Mode Dynamic Power Steering (DPS™)
SUSPENSIONS	
Front Suspension	Arched double A-arm with sway bar 22 in. (55.9 cm) suspension travel Trophy truck inspired arms
Front Shocks	FOX 2.5 PODIUM RC2 Piggyback with bypass, dual-speed compression and rebound adjustments
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar and arched lower links 24 in. (61 cm) suspension travel
Rear Shocks	FOX 3.0 PODIUM RC2 with bypass, dual-speed compression and rebound adjustments
TYRES & WHEELS	
Front	XPS Hammer King 32 x 10 x 15 in.
Rear	XPS Hammer King 32 x 10 x 15 in.
Wheels	15 in. cast-aluminum beadlock
BRAKES	
Front	Dual 262 mm disc brakes with hydraulic twin-piston calipers
Rear	Dual 248 mm disc brakes with hydraulic twin-piston calipers

DIMENSIONS & CAPACITIES

Estimated Dry Weight	1,862 lb (844.6 kg)
Chassis/Cage	Dual-phase 980 steel
LxWxH	134.5 x 72.8 x 68.5 in. (341.6 x 184.9 x 174 cm)
Wheelbase	102 in. (259.1 cm)
Ground Clearance	16 in. (40.6 cm)
Rack Capacity	200 lb (90.7 kg) with LinQ® quick-attach
Storage Capacity	Total: 2.5 gal (9.5 L)
Fuel Capacity	10.5 gal (39.7 L)
Person Capacity	2
FEATURES	

FEATURE:

Gauge	4.5 in. wide digital display with keypad & 10.25 in. touchscreen display
Instrumentation	DC outlet (10 A)
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
Lighting	LED headlight LED signature lights LED taillights
Winch	4,500 lb (2,041.2 kg) winch with synthetic cable
Magneto	850 W
Protection	Front bumper Half-doors Full hard roof Intrusion bar 4-point harness with shoulder pads UHMWPE rock sliders HMWPE skid plates: full heavy-duty with differential / under bumper / front and rear suspension arm Rear tow hook Trailing Arm protector Lower A-arm protector

WARRANTY

Factory Warranty

3-year unlimited km powertrain & Rotax* engine warranty and 1-year warranty & unlimited km on the rest of the unit



Loft Green Satin





