2026 CAN-AM MAVERICK X3 X RS TURBO RR **WITH SMART-SHOX**



PACKAGE HIGHLIGHTS

- Smart-Shox™** Technology featuring DDA Valve
- 10.25 in. touchscreen display
- Telescopic steering wheel
- Front & back cameras
 Smart-Lok™* front differential
- FOX[†] 2.5 and FOX[†] 3.0 PODIUM RC2[†] shocks with bypass
- · Belt monitoring system
- 850 W magneto
- 32 in. XPS Trac Force tyres
- 15 in. aluminum beadlock wheels
- · 4-point harness with shoulder pads
- Full hard roof

WARRANTY

- · Full heavy-duty HMWPE skid plate
- 7.6 in. digital display with keypad
- X-package graphics/seats
- · Can-Am LED signature lights
- · New skid plate and anti branch intrusion
- 2 person seating capacity

ENGINE	TURBO RR
Туре	200 hp, Rotax* ACE (Advanced Combustion Efficiency) 900 cc turbocharged triple-cylinder engine, liquid-cooled with integrated intercooler and high-performance air filter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	pDrive primary and Quick Response System X (QRS-X) CVT with high airflow, L / H / N / R / P
Drive Train	Lockable front differential with exclusive Smart-Lok™* True 2WD/4WD with front diff. lock / 4WD TRAIL ACTIV / 4WD TRAIL
Power Steering	High torque Tri-Mode Dynamic Power Steering (DPS™)
SUSPENSIONS	
Front Suspension	Arched double A-arm with sway bar 22 in. (55.9 cm) suspension travel Trophy truck inspired arms
Front Shocks	FOX 2.5 PODIUM† Piggyback with bypass and Smart-Shox Technology featuring DDA Valve (Dynamic Damping Adjustment)
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar 24 in. (61 cm) suspension travel
Rear Shocks	FOX 3.0 PODIUM [†] Piggyback with bypass and Smart-Shox Technology featuring DDA Valve (Dynamic Damping Adjustment)
TYRES & WHEELS	
Front	XPS Trac Force 32 x 10 x 15 in.
Rear	XPS Trac Force 32 x 10 x 15 in.
Wheels	15 in. cast-aluminum beadlock

Dual 262 mm disc brakes with hydraulic twin-piston calipers

Dual 248 mm disc brakes with hydraulic twin-piston calipers

DIMENSIONS & CAPACITIES		
Estimated Dry Weight	1,705 lb (773.4 kg)	
Chassis/Cage	Dual-phase 980 steel	
LxWxH	132 x 72.7 x 68.5 in. (335.3 x 184.7 x 174 cm)	
Wheelbase	102 in. (259.1 cm)	
Ground Clearance	16 in. (40.6 cm)	
Rack Capacity	200 lb (90.7 kg) with LinQ® quick-attach	
Storage Capacity	Total: 2.5 gal (9.5 L)	
Fuel Capacity	10.5 gal (39.7 L)	
Person Capacity	2	

Person Capacity	2	
FEATURES		
Gauge	4.5 in. wide digital display with keypad & 10.25 in. touchscreen display	
Instrumentation	DC outlet (10 A)	
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button	
Lighting	LED headlight LED signature lights LED taillights	
Winch	N/A	
Magneto	850 W	
Protection	Integrated front bumper Quarter-doors Full hard roof 4-point harness with shoulder pads Full heavy-duty HMWPE skid plate Rear tow hook	

Factory Warranty	3-year unlimited km powertrain & Rotax* engine warranty and 1-year warranty & unlimited km on the rest of the unit



BRAKES Front

Rear

Dusty Navy







